

- > CDAS Clean Dry Air System
- > OFAS Oil Free Air System



> COMPRESSED AIR TREATMENT
REDEFINED >





EFFICIENCY REDEFINED

Compressed air treatment has moved on: The all-new Parker Zander range of integrated drying and filtration systems is packed with innovative technology and features; delivering 100% validated air quality and world-leading standards of efficiency – in a single package.

Specified with advanced filters that include the latest OIL-X technology, every detail of the new Parker Zander CDAS (Clean Dry Air System) and the Parker Zander OFAS (Oil Free Air System) has been considered to ensure efficient operation. It means maximum productivity, total peace of mind and increased economy for industrial users - all with the reassurance of Parker engineering excellence.

 Zander

**FOCUSED ON
ADSORPTION**

 domnick
hunter

**FOCUSED ON
FILTRATION AND
SEPARATION**

Confidence redefined

Both the CDAS and OFAS are third-party validated to ISO 8573-1 (OFAS offering class 0 for total oil). No other solution offers you comparable, proven performance. So when the pressure is on, and production is in full flow, you can be 100% confident of the compressed air quality delivered.

Economy redefined

A combination of energy saving technologies, significantly reduced service times and extended maintenance periods adds up to the lowest total cost of ownership of any high quality air treatment solution. It is an all-round package designed to deliver valuable operational savings over the long term.

Productivity redefined

Highest quality compressed air; greater simplicity in parts replacement and maintenance; maximum uptime, reduced cost, greater profitability: Parker has re-engineered compressed air drying and filtration from the ground up – redefining expectations of productivity in every sense.

- Advanced form and functionality: The next generation Parker product design rationale is based around user requirements - clear information, ease of maintenance, simple operation. Everything is beautifully uncomplicated.



 Parker Zander



CDAS HL
CLEAN DRY AIR SYSTEM

› AIR TREATMENT REDEFINED ›



Innovative engineering and technology, delivering unbeatable, third-party validated performance. Pure and simple.

The new Parker Zander CDAS and OFAS ranges are the result of a unique development and design programme, which emerged from extensive market research and customer feedback. This specialist programme aimed to set a new standard for the industry – improved efficiency and productivity across the board for users.

Validated performance

Combining sophisticated OIL-X filtration technology with an optimised drying system, the CDAS and OFAS are designed to deliver consistent high performance over an extended period. CDAS and OFAS use a specialist snowstorm filling process that maximises packing density, prevents channelling effects, ensures a consistent dewpoint and contributes to an extremely low differential pressure, while air quality is third-party validated to ISO 7183 and ISO 8573-1. So you can be completely confident of your compressed air quality.

Energy efficiency

Advanced energy-saving technology is built into every unit as standard. Unlike alternative solutions, there are no expensive add-ons required to ensure minimum energy usage, regardless of the demand on air supply. Together with advanced flow management and a unique filter media offering consistently low differential pressure, it means significantly reduced energy consumption and lower running costs.

Low maintenance, long life

Enhanced durability and low maintenance are fundamental to the design of the range. The pre-stressed desiccant is specified for high crush strength and chemical compatibility, and snowstorm filled cartridges eliminate channelling, attrition, and prematurely blocked outlet filters common to loose filled designs. Plus, with a corrosion protected filter housing, guaranteed for 10 years, it all means significantly enhanced uptime, maximum productivity and a longer operational life.

Lowest total cost of ownership

Reduced energy consumption, consistent performance, lower service and maintenance costs, reduced downtime and a host of 'built in' added value features – CDAS and OFAS are engineered to provide the lowest total cost of ownership of any air treatment systems.



‹ Parker Zander OFAS – Class 0 air

Parker Zander OFAS is third-party validated by Lloyds Register to provide ISO 8573-1 Class 0 with respect to total oil from both oil lubricated and oil free compressors, ensuring the highest quality air at the point of use for critical applications, at a fraction of the cost of a dedicated oil free compressor.

› ENGINEERING & SPECIFICATION REDEFINED ›

Parker Zander CDAS, focused on adsorption – feature-rich, user-orientated design for economy of investment and effort.

›1 Threaded top end-cap

Threaded end-cap removes the need for any specialist tooling and enables the straightforward, speedy replacement of the desiccant cartridge. It means considerably faster service, resulting in less downtime.

›2 Desiccant cartridge

Snowstorm filled cartridges provide consistent drying, regeneration and dewpoint without the channelling, attrition and blocked outlet filters seen on loose filled designs – ensuring reliable performance for longer.

›3 Pre-mounted filters


New series OIL-X filters are engineered to provide validated ISO 8573-1 performance – guaranteeing consistent air quality. They are also front mounted for ease of access and minimal disruption to your operation.

›4 HMI display screen

Prominent, large screen display, offering a wealth of clear, useable, real-time information including functionality, upcoming maintenance requirements and energy savings.

›5 Base plate

Designed for pallet trucks, allowing for easy, time-saving installation and movement around the site.




Parker Zander

**FOCUSED ON
ADSORPTION**

4

5

CDASHL
CLEAN DRY AIR SYSTEM



› ENGINEERING & SPECIFICATION REDEFINED ›

Parker Zander CDAS – advanced specification and integrated technology, generating efficiency from the inside out.

›1 Corrosion protected column

Extruded aluminium column, designed to ensure a long operational life. With a 10-year guarantee, for total peace of mind, and no downtime for checking or repair.

›2 High strength desiccant


Snowstorm filled, high strength desiccant, offering 5-year lifetime, and providing consistent drying, regeneration and dewpoint - for more reliable air quality, and reduced maintenance downtime and cost.

›3 Full bore internal flow paths

Featuring optimised flow management for reduced pressure drop, improved efficiency and reduced energy costs.

›4 Full bore cylinder valve system

Low pressure loss valves provide full air flow and minimal back pressure ensuring consistent regeneration and dewpoint, whilst robust, reliable cylinders extend service intervals and lifespan, reducing total cost of ownership.





2

5 Energy saving technology

Standard on all units, it automatically adapts dryer operation to the ambient inlet conditions and compressed air demand, ensuring optimum energy consumption, full utilisation of the desiccant material, and a 5-year valve lifetime. The result is reduced maintenance and significantly lower energy costs - often with savings of up to 85%.



4



5



Parker | domnick hunter

Parker | domnick hunter

Parker | domnick hunter

› FILTRATION REDEFINED ›



A new series of compressed air filters, taking efficiency to a different level, and offering game-changing advantages for users.

The Parker domnick hunter OIL-X has been developed in tandem with the Parker Zander CDAS and OFAS dryer ranges, and shares an identical design philosophy: simplicity, compatibility and usability, but above all validated air quality.

OIL-X is available in four different variants: water separation, coalescing, dry particulate and oil vapour removal.

Validated performance you can rely on

Built on Parker's worldwide expertise in filtration, the Parker domnick hunter OIL-X range has been developed to ensure consistent outstanding air quality, guaranteed for 12 months - and third-party validated to meet ISO 8573-1 (the international standard of compressed air quality).

Lowest differential pressure

Combining the unique filter element with a specially designed advanced air flow management system, the Parker domnick hunter OIL-X range is engineered to not only deliver air quality in accordance with ISO 8573-1 classifications, but it does so with an extremely low differential pressure – ensuring maximum efficiency and productivity.

Cost savings

Extended equipment lifespan, reduced maintenance, enhanced energy efficiency, proven reliability and minimal downtime all contribute towards lowest total cost of ownership – and a significant positive impact on compressed air running costs.

Versatility

Whilst designed to work as an integral component of our advanced air treatment systems, Parker domnick hunter OIL-X filters are also a drop-in replacement for the OIL-X Plus, and are fully retro-compatible with a wide range of drying equipment. They are also approved for use in many different markets and applications.



› PRODUCT DESIGN REDEFINED ›

Parker domnick hunter OIL-X, focused on filtration and separation – delivering efficiency, validated air quality and cost savings, through the simplicity of great engineering and forward thinking product design.

›1 Unique filter element

With a specialist construction and unique design for reduced air flow velocity, reduced pressure loss, increased dirt holding capacity, and improved efficiency – including a 12-month air quality guarantee.

›2 Flow management system

Specially engineered 'bell mouth', with 90-degree elbow, flow distributor and conical flow diffusor, to promote a consistent, optimum air flow, contributing towards maximum efficiency, reduced differential pressure and lower energy consumption.

>3 Filter housing

Designed to allow easy maintenance and element replacement, and covered by a 10-year guarantee, for reduced downtime, service cost and peace of mind.

>4 Flexible connections

A wide range of port sizes and filter connections, for added flexibility and time saving.

>5 Epoxy coating

Finished with alocrom corrosion protection and a tough, dry powder epoxy coating for a high quality feel with the reassurance of durability.



The image shows two vertical air treatment units from Parker Zander. Each unit consists of a grey cylindrical main body with a yellow control head at the top. The control head features a digital display showing two vertical bars, one blue and one green, and two analog pressure gauges. The units are mounted on a grey base with yellow fittings. The background is a light grey with a faint, stylized image of a car wheel.

CDAS HL
CLEAN DRY AIR SYSTEM

OFAS HL
OIL FREE AIR SYSTEM

Parker Zander

Parker Zander

EFFICIENT SOLUTIONS REDEFINED

The new range of Parker air treatment systems change the way you think about compressed air quality. Designed for improved efficiency in every respect – it's an opportunity to improve the productivity, reliability and profitability of your operation.



Class leading specification

A complete package of technology and engineering excellence, for outstanding air quality, operational control and energy efficiency.

Low maintenance

Designed for faster, simpler, less frequent maintenance; reducing downtime, extending product lifetime and helping your investment go further.

Complete confidence

The only systems with third-party validation – clean dry air and oil free air to ISO 8573-1. Providing you with total confidence in your air quality.

Total affordability

Added value standard specification (including Energy Saving Technology), reduced maintenance, increased uptime, energy efficiency - delivering the lowest total cost of ownership in the marketplace.

WHAT NEXT?

Discover how Parker's advanced air treatment systems could enhance your productivity, environmental performance, and business efficiency. Visit www.parker.com/cdas



Parker Worldwide

Europe, Middle East, Africa

AE – United Arab Emirates,
Dubai

Tel: +971 4 8127100
parker.me@parker.com

AT – Austria, Wiener Neustadt
Tel: +43 (0)2622 23501-0
parker.austria@parker.com

AT – Eastern Europe, Wiener
Neustadt
Tel: +43 (0)2622 23501 900
parker.easteurope@parker.com

AZ – Azerbaijan, Baku
Tel: +994 50 2233 458
parker.azerbaijan@parker.com

BE/LU – Belgium, Nivelles
Tel: +32 (0)67 280 900
parker.belgium@parker.com

BG – Bulgaria, Sofia
Tel: +359 2 980 1344
parker.bulgaria@parker.com

BY – Belarus, Minsk
Tel: +48 (0)22 573 24 00
parker.poland@parker.com

CH – Switzerland, Etoy
Tel: +41 (0)21 821 87 00
parker.switzerland@parker.com

CZ – Czech Republic, Klecany
Tel: +420 284 083 111
parker.czechrepublic@parker.com

DE – Germany, Kaarst
Tel: +49 (0)2131 4016 0
parker.germany@parker.com

DK – Denmark, Ballerup
Tel: +45 43 56 04 00
parker.denmark@parker.com

ES – Spain, Madrid
Tel: +34 902 330 001
parker.spain@parker.com

FI – Finland, Vantaa
Tel: +358 (0)20 753 2500
parker.finland@parker.com

FR – France, Contamine s/Arve
Tel: +33 (0)4 50 25 80 25
parker.france@parker.com

GR – Greece, Athens
Tel: +30 210 933 6450
parker.greece@parker.com

HU – Hungary, Budaörs
Tel: +36 23 885 470
parker.hungary@parker.com

IE – Ireland, Dublin
Tel: +353 (0)1 466 6370
parker.ireland@parker.com

IL – Israel
Tel: +39 02 45 19 21
parker.israel@parker.com

IT – Italy, Corsico (MI)
Tel: +39 02 45 19 21
parker.italy@parker.com

KZ – Kazakhstan, Almaty
Tel: +7 7273 561 000
parker.easteurope@parker.com

NL – The Netherlands, Oldenzaal
Tel: +31 (0)541 585 000
parker.nl@parker.com

NO – Norway, Asker
Tel: +47 66 75 34 00
parker.norway@parker.com

PL – Poland, Warsaw
Tel: +48 (0)22 573 24 00
parker.poland@parker.com

PT – Portugal
Tel: +351 22 999 7360
parker.portugal@parker.com

RO – Romania, Bucharest
Tel: +40 21 252 1382
parker.romania@parker.com

RU – Russia, Moscow
Tel: +7 495 645-2156
parker.russia@parker.com

SE – Sweden, Spånga
Tel: +46 (0)8 59 79 50 00
parker.sweden@parker.com

SK – Slovakia, Banská Bystrica
Tel: +421 484 162 252
parker.slovakia@parker.com

SL – Slovenia, Novo Mesto
Tel: +386 7 337 6650
parker.slovenia@parker.com

TR – Turkey, Istanbul
Tel: +90 216 4997081
parker.turkey@parker.com

UA – Ukraine, Kiev
Tel: +48 (0)22 573 24 00
parker.poland@parker.com

UK – United Kingdom, Warwick
Tel: +44 (0)1926 317 878
parker.uk@parker.com

ZA – South Africa, Kempton Park
Tel: +27 (0)11 961 0700
parker.southafrica@parker.com

North America

CA – Canada, Milton, Ontario
Tel: +1 905 693 3000

US – USA, Cleveland
Tel: +1 216 896 3000

Asia Pacific

AU – Australia, Castle Hill
Tel: +61 (0)2-9634 7777

CN – China, Shanghai
Tel: +86 21 2899 5000

HK – Hong Kong
Tel: +852 2428 8008

IN – India, Mumbai
Tel: +91 22 6513 7081-85

JP – Japan, Tokyo
Tel: +81 (0)3 6408 3901

KR – South Korea, Seoul
Tel: +82 2 559 0400

MY – Malaysia, Shah Alam
Tel: +60 3 7849 0800

NZ – New Zealand, Mt Wellington
Tel: +64 9 574 1744

SG – Singapore
Tel: +65 6887 6300

TH – Thailand, Bangkok
Tel: +662 186 7000

TW – Taiwan, Taipei
Tel: +886 2 2298 8987

South America

AR – Argentina, Buenos Aires
Tel: +54 3327 44 4129

BR – Brazil, Sao Jose dos Campos
Tel: +55 800 727 5374

CL – Chile, Santiago
Tel: +56 2 623 1216

MX – Mexico, Toluca
Tel: +52 72 2275 4200

European Product Information Centre
Free phone: 00 800 27 27 5374

(from AT, BE, CH, CZ, DE, DK, EE, ES, FI,
FR, IE, IL, IS, IT, LU, MT, NL, NO, PL, PT, RU,
SE, SK, UK, ZA)